

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 March 2001 (29.03.2001)

PCT

(10) International Publication Number
WO 01/21558 A1

- (51) International Patent Classification?: C06C 7/00 (74) Agent: JIROTKOVÁ, Ivana; Rott, Ruzicka & Guttman, P.O. Box 71, 142 00 Praha 4 (CZ).
- (21) International Application Number: PCT/CZ00/00067
- (22) International Filing Date:
11 September 2000 (11.09.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
PV 1999-3305 17 September 1999 (17.09.1999) CZ
- (71) Applicant (for all designated States except US): SEL-
LIER & BELLOT, A.S. [CZ/CZ]; Lidická 667, 258 13
Vlašim (CZ).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): NESVEDA, Jiří
[CZ/CZ]; Havlíčkova 1596, 258 01 Vlašim (CZ). BRAN-
DEJS, Stanislav [CZ/CZ]; Zámecká 1490, 258 01 Vlašim
(CZ). JIRÁSEK, Karel [CZ/CZ]; 258 01 Kondrac 85
(CZ).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,
TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:
— With international search report.
- For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: NON-TOXIC AND NON-CORROSIVE IGNITION MIXTURE

(57) Abstract: A non-toxic and non-corrosive ignition mixture is created by combining the energy system and the pyrotechnic system. The energy system comprises a high explosive from the groups of nitroesters and nitramines and a sensibiliser of the type of tetrazene or derivatives of tetrazoles for its activation. The pyrotechnic system comprises an oxidizing agent from the group of oxides and peroxides of metals, from the group of salts of inorganic oxygen-containing acids, and a fuel which is amorphous boron. The mixture is supplemented with a friction agent which is preferably ground glass. Nitrocellulose, polyvinyl alcohol and acacia gum are used as bonding agents. Mixtures are utilizable in the field of ammunition production for the production of primers, especially for central ignition cartridges.

WO 01/21558 A1

Non-toxic and non-corrosive ignition mixture

Technical field

The invention concerns the field of ammunition production, especially the production of ignition mixtures for hunting and sports ammunition.

Background Art

All sorts of known ignition mixtures, which are presently used, i.e. both already dated mixtures based on mercuric fulminate, calcium chlorate and antimony sulphide, and newer non-corrosive mixtures based on tetrazene, lead trinitroresorcinate, lead dioxide, calcium silicide and antimony sulphide, emit during discharge a large amount of toxic heavy metals and they do not meet the environmental standards. That is why an extensive research has been carried out in the last ten years with an aim to develop a mixture that would not contain compounds of heavy metals such as lead, barium, mercury, antimony, and, at the same time, would retain non-corrosive properties of trinitrate mixtures. The result is a mixture in which an aromatic diazo compound without metal content – dinol - fulfils the function of a primary explosive and tetrazene remains as a sensitizer. The pyrotechnic system is in this case composed of a new oxidizing agent, zinc peroxide and titanium powder. The mixture can contain also other components such as friction agents, typically ground glass, and active propellants such as various sorts of nitrocellulose and nitroglycerine powders. Mixtures based on dinol are also known in which basically only the pyrotechnic system is modified. Oxidizing agents used include various oxides of metals – potassium nitrate, strontium nitrate, basic nitrates of copper and copper-ammonium nitrate and tin compounds. Neither these mixtures are a final solution. The basic problem here is the primary explosive itself – dinol. It is a carcinogenic compound with very unpleasant physiological effects. That is why there have been noted attempts to avoid dinol completely. EP 0656332 A1, in which the mixture is based only on pyrotechnic system and does not contain any explosive, offers one such solution. Here, the propellant is a hyperactive zircon powder, the oxidizing agent is a mixture of potassium nitrate and manganese dioxide, and the energy component is penthrite.

-2-

There is no doubt that this mixture is according to the data of the inventors fully functional even though here a serious problem can also arise. It can be zircon itself. As the inventors themselves state, the active form of zircon is ignited by the influence of minute energy impulse both mechanically and thermally. It is well known that highly active metal powders, especially zircon, are pyrophoric and extremely reactive. They react both with air oxygen creating oxides and with air nitrogen creating nitrides and also with humidity creating hydrides. During transportation and storage, they have to be stored under water and during the production of mixtures water must be displaced using a water-immiscible organic solvent. According to the inventors, isopropyl alcohol is the most advantageous. The technology is then based on classical embrocating of pasty mixture into primer caps, however with the difference that the bonding agent is not an aqueous solution of the given organic compound but a solution of aerosil in isopropyl alcohol. During the production and the feeding of such mixtures, serious problems can arise such as handling extremely reactive zircon and moreover also technological problems resulting from the use of large amounts of organic solvents during the production.

Disclosure of the Invention

The above drawbacks are solved and totally removed by a non-toxic and non-corrosive ignition mixture the essence of which lies in that in the energy system, the primary explosive of the dinol type is replaced by a high explosive, which is activated by a sensitizer of the tetrazene type or by salts and derivatives of tetrazoles. Nitroesters such as penthrite and hexanitromanite but also nitrocellulose in the form of granulate and also nitroamines such as hexogene, octogene and tetryle, can be used as the high explosive. In order to increase the ignition power, the mixture must be supplemented with an appropriate pyrotechnic system. Mixtures with powder boron turned out to be the most suitable, especially those with brown, so-called amorphous, boron with large specific surface which in the case of commonly available specimens reaches 5 to 25 m²/g. Extensive testing has proven that amorphous boron is an excellent fuel and that it is able to create a perfect redox-system with any metal oxide, independent of valence, further with metal peroxides and all known salts of inorganic oxygen-containing acids.

Into the pyrotechnic system with boron, oxidizing agents can be selected from the group of compounds such as oxides of univalent metals: cuprous (I) - Cu₂O, bivalent: cupric (II) -

-3-

CuO, zinc (II) - ZnO, oxides of multivalent metals: bismuth (III) - Bi_2O_3 , bismuth (IV) - BiO_2 and bismuth (V) - Bi_2O_5 , ferric (III) - Fe_2O_3 , manganese (IV) - MnO_2 , stannic (IV) - SnO_2 , vanadic (V) - V_2O_5 and molybdenum (VI) - MoO_3 , peroxides of zinc - ZnO_2 and calcium - CaO_2 , saltpetre - KNO_3 and some special salts such as basic bismuth nitrates - $4\text{BiNO}_3(\text{OH})_2$, $\text{BiO}(\text{OH})$ and $\text{BiONO}_3 \cdot \text{H}_2\text{O}$, basic copper nitrate - $\text{Cu}(\text{NO}_3)_2 \cdot 3\text{Cu}(\text{OH})_2$, diammo-copper nitrate - $\text{Cu}(\text{NH}_3)_2(\text{NO}_3)_2$, basic tin nitrate - $\text{Sn}_2\text{O}(\text{NO}_3)_2$. Boron creates the fastest burning system with compounds of bismuth. Systems with the highest heating effect originate when potassium nitrate, cupric oxide, ferric oxide and manganese oxide are used. The products of combustion can be both low-melting boron (III) oxide - B_2O_3 and volatile boron (II) oxide - BO which is more stable at higher temperatures, possibly also boron nitride - BN. The presence of these compounds in the products of combustion is very desirable from the viewpoint of perfect ignition of powder cartridge charges. In spite of its extraordinary reactivity, boron is chemically stable and it is not dangerous for handling. The expenses related to boron are compensated by its minimal content in stoichiometric mixtures, which does not exceed 20 weight percent. In order to increase sensitivity to strike by a blow, it is necessary to supplement the mixture with an appropriate friction agent, which is ground glass.

Considering that ignition mixtures produced in this way are in a very fine form it seems that the most suitable technology is handling when wet and, therefore, the mixture can also contain a certain amount of a water-soluble bonding agent. Commonly known bonding agents such as acacia gum, dextrin, polyvinyl alcohol, carboxymethyl cellulose and others are the most suitable. Should it be necessary to handle the mixture when dry, it would need to be granulated first. Granulation can be done both by using the above-mentioned bonding agents in water solutions or by using bonding agents soluble in organic solvents, e.g. nitrocellulose in acetone. The pyrotechnic system can be also grained after pressing and the grained product can be later used in the mixtures. In this case, the mixture does not have to contain any bonding agent because it can be easily fed when dry.

Within several years extensive tests have been performed both with primer caps filled with mixtures of the invention and with ammunition equipped with these primer caps.

The results of said functional tests show that it is possible, by a suitably chosen combination of the energy and pyrotechnic systems, to achieve desired characteristics of the mixture for a particular type of the primer. For example, for the smallest types of primer caps having the shortest reaction times, destined for the pistol and revolver ammunitions, it is necessary that

-4-

the energy and pyrotechnic systems show as high reactivity as possible and have a high energy content at the same time. Primers showing the highest reactivity include nitro esters, which can be most easily initiated, among them mainly mannite hexanitrate, which is however predestined for special use due to its high cost and somewhat lower chemical stability. On the other hand, penthrite has shown itself as an ideal explosive with a wide range of utility. Similarly, nitrocellulose is a universal and multipurpose explosive, which can play roles of the combustible, the propellant and the binder at the same time. Nitramines are at a lower level in terms of effect than nitro esters and their initiability is lower. This renders them useful in primer caps having larger dimensions and longer reaction times, wherein they can be applied better than nitro esters, the very high effect of which could even be disadvantageous in some cases.

For comparison, results are presented of measurements of the primer caps 4.4/0.4 BOXER, destined for cartridges 9 mm LUGER, by the method DROP-TEST, in which we obtained a graphical function of the pressure values in dependence on the reaction time of the primer. The mixture of Example 20 was compared to a classical mixture based on lead trinitroresorcinat, the charge of which in the primer cap is by about 20 % higher. For both mixtures, identical values were obtained for maximal pressures - 100 bars - and reaction times - 100 microseconds.

Parameters of inner ballistics of the cartridge 9 mm LUGER with the primer cap filled with the above-described mixture were also measured. When a suitably chosen powder is used, it is possible, for a bullet weighing 7.5 g, to achieve muzzle velocities about 420 m/s without exceeding admissible values of maximal pressures in the chamber. Besides, functional shootings from various types of short and automatic weapons were performed, wherein the inventive ammunition showed reliable functioning.

It has been found that the mixtures of the invention, which contain tetrazene as the main explosive, show extraordinary handling safety. During burning of this mixture no development has been observed of any toxic combustion gases or compounds able to cause corrosion of the weapon.

Ignition mixtures created by combination of energy and pyrotechnic systems according to the mentioned essence of the invention are expressed by the following scheme:

data are presented in weight percentages

- high explosive 5 to 40 %

-5-

- senzibilizer	5 to 40 %
- oxidizing agent	5 to 50 %
- boron	1 to 20 %
- friction agent	5 to 30 %
- possible bonding agent	0.1 to 5 %

Examples

The make is presented in weight percentages.

Example 1 – mixture without a bonding agent, suitable for handling when dry

tetrazene	25 %
penthrite	25 %
$4\text{BiNO}_3(\text{OH})_2 \cdot \text{BiO}(\text{OH})$	36.4 %
B	3.6 %
ground glass	10 %

Example 2 – similar mixture with higher sensitivity

a) dry variant – without bonding agent		b) wet variant	
tetrazene	35 %	tetrazene	35 %
penthrite	05 %	penthrite	05 %
$4\text{BiNO}_3(\text{OH})_2 \cdot \text{BiO}(\text{OH})$	18 %	$4\text{BiNO}_3(\text{OH})_2 \cdot \text{BiO}(\text{OH})$	18 %
B	2 %	B	2 %
glass	10 %	acacia gum	0.5 %
		glass	19.5 %

Example 3 – similar mixture

a) dry variant		b) wet variant	
tetrazene	25 %	tetrazene	25 %
penthrite	25 %	tetryle	25 %
$\text{BiONO}_3 \cdot \text{H}_2\text{O}$	34 %	$\text{BiONO}_3 \cdot \text{H}_2\text{O}$	34 %
B	5.5 %	B	5.5 %
glass	10 %	acacia gum	0.5 %

-6-

nitrocellulose	0.5 %	glass	10 %
----------------	-------	-------	------

Example 4 – mixture with higher heating effect

a) dry variant – without bonding agent

tetrazene	35 %
penthrite	15 %
CuO	34 %
B	6 %
glass	10 %

b) wet variant

tetrazene	25 %
penthrite	25 %
CuO	34 %
B	5.5 %
polyvinyl alcohol	0.5 %
glass	10 %

Example 5

a) dry variant

tetrazene	35 %
penthrite	15 %
Bi ₂ O ₃	36 %
B	3.5 %
nitrocellulose	0.5 %
glass	10 %

b) wet variant

tetrazene	25 %
hexogene	25 %
Bi ₂ O ₃	36 %
B	3.5 %
polyvinyl alcohol	0.5 %
glass	10 %

Example 6

a) dry variant

tetrazene	35 %
penthrite	15 %
MnO ₂	31.5 %
B	8 %
nitrocellulose	0.5 %
glass	10 %

b) wet variant

tetrazene	25 %
tetryle	25 %
MnO ₂	31.5 %
B	8 %
acacia gum	0.5 %
glass	10 %

Example 7

a) dry variant

tetrazene	25 %
penthrite	25 %

b) wet variant

tetrazene	25 %
penthrite	25 %

-7-

ZnO	34 %
B	5.5 %
nitrocellulose	0.5 %
glass	10 %

ZnO	34 %
B	5.5 %
acacia gum	0.5 %
glass	10 %

Example 8

only dry variant

tetrazene	25 %
penthrite	25 %
Fe ₂ O ₃	34 %
B	5.5 %
nitrocellulose	0.5 %
glass	10 %

Example 9

a) dry variant

tetrazene	25 %
penthrite	25 %
V ₂ O ₅	30 %
B	9.5 %
nitrocellulose	0.5 %
glass	10 %

b) wet variant

tetrazene	25 %
penthrite	25 %
V ₂ O ₅	30 %
B	9.5 %
acacia gum	0.5 %
glass	10 %

Example 10

a) dry variant

tetrazene	35 %
penthrite	15 %
SnO ₂	34 %
B	5.5 %
nitrocellulose	0.5 %
glass	10 %

b) wet variant

tetrazene	25 %
penthrite	25 %
SnO ₂	34 %
B	5.5 %
acacia gum	0.5 %
glass	10 %

-8-

Example 11

a) dry variant

tetrazene	25 %
penthrite	25 %
MoO ₃	30 %
B	9.5 %
nitrocellulose	0.5 %
glass	10 %

b) wet variant

tetrazene	25 %
penthrite	25 %
MoO ₃	30 %
B	9.5 %
acacia gum	0.5 %
glass	10 %

Example 12

a) dry variant

tetrazene	25 %
penthrite	25 %
ZnO ₂	30 %
B	9.5 %
nitrocellulose	0.5 %
glass	10 %

b) wet variant

tetrazene	25 %
tetryle	25 %
ZnO ₂	30 %
B	9.5 %
polyvinyl alcohol	0.5 %
glass	10 %

Example 13

only dry variant

tetrazene	25 %
hexogene	25 %
CaO ₂	30 %
B	9.5 %
nitrocellulose	0.5 %
glass	10 %

Example 14

only dry variant – mixture with higher heating effect

tetrazene	25 %
penthrite	25 %
KNO ₃	33.5 %
B	6 %

-9-

nitrocellulose	0.5 %
glass	10 %

Example 15

a) dry variant

tetrazene	35 %
penthrite	15 %
$\text{Cu}(\text{NO}_3)_2 \cdot 3\text{Cu}(\text{OH})_2$	31.5 %
B	8 %
nitrocellulose	0.5 %
glass	10 %

b) wet variant

tetrazene	25 %
hexogene	25 %
$\text{Cu}(\text{NO}_3)_2 \cdot 3\text{Cu}(\text{OH})_2$	31.5 %
B	8 %
acacia gum	0.5 %
glass	10 %

Example 16

a) dry variant

tetrazene	35 %
penthrite	15 %
$\text{Cu}(\text{NH}_3)_2(\text{NO}_3)_2$	27.5 %
B	12 %
nitrocellulose	0.5 %
glass	10 %

b) wet variant

tetrazene	25 %
hexogene	25 %
$\text{Cu}(\text{NH}_3)_2(\text{NO}_3)_2$	27.5 %
B	12 %
acacia gum	0.5 %
glass	10 %

Example 17 – with highly reactive oxidizing agent

a) dry variant

tetrazene	25 %
penthrite	25 %
BiO_2	33.5 %
B	6 %
nitrocellulose	0.5 %
glass	10 %

b) wet variant

tetrazene	25 %
hexogene	25 %
BiO_2	33.5 %
B	6 %
acacia gum	0.5 %
glass	10 %

Example 18 – analogous mixture

a) dry variant

tetrazene	25 %
-----------	------

b) wet variant

tetrazene	25 %
-----------	------

-10-

penthrite	25 %	tetryle	25 %
Bi ₂ O ₅	33 %	Bi ₂ O ₅	33 %
B	6.5 %	B	6.5 %
nitrocellulose	0.5 %	acacia gum	0.5 %
glass	10 %	glass	10 %

Example 19 – a specific case where oxidizing agent works as auxiliary explosive

a) dry variant

tetrazene	25 %
penthrite	25 %
Sn ₂ O(NO ₃) ₂	32 %
B	8 %
glass	10 %

b) wet variant

tetrazene	25 %
hexogene	25 %
Sn ₂ O(NO ₃) ₂	31.5 %
B	8 %
acacia gum	0.5 %
glass	10 %

Example 20

use of two oxidizing agents

tetrazene	30 %
penthrite	7.5 %
4BiONO ₃ (OH) ₂ .BiO(OH)	18 %
KNO ₃	17 %
B	5 %
nitrocellulose	0.5 %
glass	22 %

Industrial applicability

Mixtures that are in accordance with technical solution are utilizable in the field of ammunition production for the production of primers for central ignition cartridges intended for sports, hunting and practice purposes, or for shooting cartridges.

CLAIMS

1. A non-toxic and non-corrosive ignition mixture created by combining the energy system with the pyrotechnic system characterized by the fact that the mixture composed of the energy and pyrotechnic systems comprises 5 up to 40 weight percent of a high explosive, selected from the group of nitroesters and nitramines, 5 up to 40 weight percent of a sensibilizer, which is tetrazene or salts or derivatives of tetrazoles, 5 up to 50 % of an oxidizing agent selected from the group of oxides and peroxides of metals or from the group of salts of inorganic oxygen-containing acids or from the group of complex salts, 1 up to 20 weight percent of boron as a fuel, 5 up to 30 weight percent of a friction agent and optionally 0,1 up to 5 weight percent of a bonding agent.
2. The mixture according to claim 1 characterized by the fact that the high explosive is selected from the group of nitroesters such as penthrite, hexanitromannite, nitrocellulose, or from the group of nitramines such as hexogene, octogene, tetryle.
3. The mixture according to claim 1 characterized by the fact that the fuel is amorphous boron with specific surface of 5 up to 25 m²/g.
4. The mixture according to claim 1 characterized by the fact that the oxidizing agent is selected from the group of metal oxides such as oxides of copper, zinc, bismuth, iron, manganese, tin, vanadium and molybdenum, or from the group of metal peroxides such as peroxides of zinc and calcium, or from the group of salts of inorganic oxygen-containing acids such as saltpetre, basic nitrates of bismuth, tin and copper, or from the group of complex salts such as diammo-copper nitrate.
5. The mixture according to claim 1 characterized by the fact that the bonding agents are nitrocellulose, polyvinyl alcohol or acacia gum.

-12-

6. The mixture according to claims 2 and 5 characterized by the fact that nitrocellulose applied in the organic solvent such as acetone functions, at the same time, as the bonding agent and energy component.
7. The mixture according to claim 1 characterized by the fact that the friction agent is ground glass.

INTERNATIONAL SEARCH REPORT

Internat. Application No

PCT/CZ 00/00067

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C06C7/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C06C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 167 736 A (G.C. MEI ET AL.) 1 December 1992 (1992-12-01) claims	1-7
Y	US 5 216 199 A (R.K. BJERKE ET AL.) 1 June 1993 (1993-06-01) claims	1-7
A	US 5 547 528 A (J.A. ERICKSON ET AL.) 20 August 1996 (1996-08-20) column 2, line 34 - line 39 column 3, line 47 - line 59; claims 20-25	1-7
A	FR 2 021 662 A (DYNAMIT NOBEL AKTIENGESELLSCHAFT) 24 July 1970 (1970-07-24) claims	1-7
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

28 December 2000

Date of mailing of the international search report

05/01/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Schut, R

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CZ 00/00067

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 12 43 067 B (INDUSTRIE-WERKE KARLSRUHE AKTIENGESELLSCHAFT) claims ---	3
A	US 5 567 252 A (G.C. MEI ET AL.) 22 October 1996 (1996-10-22) claims -----	1-7

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/CZ 00/00067

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5167736 A	01-12-1992	AT 162167 T	15-01-1998
		AU 662770 B	14-09-1995
		AU 2907592 A	07-06-1993
		BG 61604 B	30-01-1998
		BG 98746 A	31-05-1995
		BR 9206708 A	24-10-1995
		CA 2122710 A	13-05-1993
		CZ 9401100 A	15-12-1994
		DE 69224081 D	19-02-1998
		DE 69224081 T	13-08-1998
		DK 660812 T	09-02-1998
		EP 0660812 A	05-07-1995
		ES 2111084 T	01-03-1998
		FI 942051 A	04-05-1994
		HK 1008424 A	07-05-1999
		HU 68124 A, B	29-05-1995
		JP 7500562 T	19-01-1995
		KR 242749 B	01-02-2000
		NO 941631 A	03-05-1994
		RO 112423 B	30-09-1997
		RU 2127238 C	10-03-1999
		SK 51094 A	09-11-1994
		WO 9309073 A	13-05-1993
US 5216199 A	01-06-1993	AT 161943 T	15-01-1998
		BR 9202626 A	16-03-1993
		CA 2067302 A	09-01-1993
		DE 69223881 D	12-02-1998
		DE 69223881 T	16-04-1998
		DK 529230 T	27-04-1998
		EP 0529230 A	03-03-1993
		ES 2111586 T	16-03-1998
		GR 3025843 T	30-04-1998
		MX 9203997 A	01-01-1993
		ZA 9202779 A	30-12-1992
US 5547528 A	20-08-1996	AU 7103296 A	18-12-1996
		CA 2222065 A	05-12-1996
		EP 0828698 A	18-03-1998
		NO 975389 A	22-01-1998
		WO 9638397 A	05-12-1996
FR 2021662 A	24-07-1970	DE 1805358 A	18-06-1970
		BE 740680 A	01-04-1970
		CH 536798 A	15-05-1973
		GB 1284912 A	09-08-1972
		NL 6915133 A	28-04-1970
		NO 121321 B	08-02-1971
DE 1243067 B		NONE	
US 5567252 A	22-10-1996	NONE	